



Standard Compliances

- ISO/IEC 11801:2002(Ed.2.0), including amendments A1:2008 and A2:2010
- IEC 61156-5:2009(Ed.2.0)
- EN 50173-1:2011
- EN 50173-2:2007 including amendment A1:2010
- ANSI/TIA-568-C.2:2009

Features and Benefits

- Ideal solution for 10Gigabit Ethernet
- Individual pair shielding or special designed filler to provide EMI protection
- Designed with shielding to offer maximum pair separation, increasing key electrical performance parameters
- Provides positive PSACR beyond 500MHz for higher available bandwidth
- Every master reel is tested to ensure electrical performance compliance
- Print legend contains footage marking from 305M to 0M or 500M to 0M
- Unique product-specific packaging for ease of identification
- RoHS compliant
- EC Verified

Applications

- 2.4/1.2 Gb/s ATM
- IEEE 802.3an:10G BAST-T (10 Gigabit Ethernet) supporting 100 meters
- 3D imaging
- Digital Video
- Broadband and Baseband Analog Video

Order Information

Part No.	No. of Pairs	Cable Type	Conductor Size	Core Dimension (mm)	Overall Dimension (mm)
66504A	4	U-UTP	23AWG	1.05	7.80 * 9.20
66304A	4	F-FTP	23AWG	1.28	7.39
66904A	4	S-FTP	23AWG	1.28	7.76

Jacket / PVC • LSZH (Low Smoke Zero Halogen) • Outdoor PE